

Product datasheet

Specifications



RIO drop adaptor module Modicon Quantum - 2 connectors with redundant cable

140CRA93200

! Discontinued - Service only

! Discontinued on: 14-Apr-2023

! To be end-of-service on: 31-Dec-2030

Main

| | |
|---------------------------|-------------------------------------|
| Range of product | Modicon Quantum automation platform |
| Product or component type | RIO drop adaptor module |

Complementary

| | |
|--|--|
| Product compatibility | Quantum |
| Maximum number of I/O expansion module | 27 |
| Type of cable | 75 Ohm coaxial cable |
| Transmission rate | 1544 Mbit/s |
| Dynamic range | 35 dB |
| Isolation voltage | 500 V DC coaxial center and ground |
| Electrical connection | 2 female connectors F, elbowed with redundant cable |
| Diagnostics startup | Power up and runtime RAM address/data Executive checksum |
| Power dissipation in W | 3.8 W 2 channels |
| Bus current requirement | 750 mA 2 channels |
| Module format | Standard |

Environment

| | |
|---------------------------------------|---|
| Standards | UL 508 CUL CSA C22.2 No 142 |
| Resistance to electrostatic discharge | 4 kV contact conforming to IEC 801-2 8 kV on air conforming to IEC 801-2 |
| Resistance to electromagnetic fields | 10 V/m 80...1000 MHz conforming to IEC 801-3 |
| Ambient air temperature for operation | 0...60 °C |
| Ambient air temperature for storage | -40...85 °C |
| Relative humidity | 95 % without condensation |
| Operating altitude | <= 5000 m |

Packing Units

| | |
|------------------------|-----|
| Unit Type of Package 1 | PCE |
|------------------------|-----|

| | |
|-------------------------------------|-----------|
| Number of Units in Package 1 | 1 |
| Package 1 Height | 5.000 cm |
| Package 1 Width | 16.500 cm |
| Package 1 Length | 31.500 cm |
| Package 1 Weight | 545.000 g |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty | 18 months |
|-----------------|-----------|

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



RoHS/REACH

Well-being performance

Reach Free Of Svhc

Mercury Free

Rohs Exemption Information Yes

Certifications & Standards

Eu Rohs Directive Pro-active compliance (Product out of EU RoHS legal scope)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)


Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)

Dimensions Drawings

Racks for Modules Mounting

Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots